

**产品规格书****Specification of Product**

产品名称: 8.4V 40kg数字舵机

Product Name: 8.4V 40kg.cm High voltage Digital Servo

产品型号 Model No. FT5335M

1. 使用环境条件 Apply Environmental Condition

No.	Item	Specification
1-1	存储温度 Storage Temperature Range	-30°C~80°C
1-2	运行温度 Operating Temperature Range	-15°C~70°C

2. 测试环境 Standard Test Environment

No.	Item	Specification
2-1	温度 Temperature range	25°C ±5°C
2-2	湿度 Humidity range	65%±10%

3. 机械特性 Mechanical Specification

No.	Item	Specification
3-1	尺寸 Size	A: 62.8mm B: 32.5mm C: 55.9mm
3-2	重量 Weight	178g ±0.2
3-3	齿轮类型 Gear type	Metal Gear
3-6	机构极限角度 Limit angle	180degree
3-7	轴承 Bearing	2BB
3-8	出力轴 Horn gear spline	25T(5.8mm)
3-9	摆臂 Horn type	Plastic, POM
3-10	外壳 Case	Engineering plastics+Aluminium
3-11	舵机线 Connector wire	300mm ±5 mm
3-12	马达 Motor	Core motor
3-13	防水性能 Splash water resistance	NO

4. 电气特性 Electrical Specification (Function of the Performance)

No.	工作电压 Operating Voltage Range	6V	8.4V
4-1*	静态电流 Idle current(at stopped)	8mA	9mA
4-2*	空载速度 No load speed	0.20sec/60degree	0.18sec/60degree
4-3*	空载电流 Runnig current(at no load)	250 mA	280 mA
4-4	堵转扭矩 Peak stall torque	32.5kg.cm	40.5kg.cm
		451.33oz.in	562.43oz.in
4-5	堵转电流 Stall current	2000 mA	2400mA

Note: "*"definition is average value when the servo runing with no load



产品规格书

Specification of Product

产品名称: 8.4V 40kg数字舵机

Product Name: 8.4V 40kg.cm High voltage Digital Servo

产品型号 Model No. FT5335M

5. 控制特性 Control Specification:

No.	Item	Specification
5-1	控制信号 Command signal	Pulse width modification
5-2	放大器类型 Amplifier type	Analog comparator
5-3	脉冲宽度范围 Pulse width range	900~2100μsec
5-4	中立位置 Neutral position	1500μsec
5-5	旋转角度 Running degree	120° (when 900~2100 μ sec)
5-6	死区宽度 Dead band width	2 μsec
5-7	旋转方向 Rotating direction	CW(when 1500~900 μsec) CCW(when 1500~2100 μsec)

6. 外形图 The Drawings

